

**SYSTEM AND METHOD FOR COMMUNICATING OPTICAL SIGNALS
BETWEEN A DATA SERVICE PROVIDER AND SUBSCRIBERS**

PRIORITY CLAIM TO PROVISIONAL APPLICATIONS

5 The present application claims priority to provisional patent application
entitled, "Systems to Provide Video, Voice and Data Services via Fiber Optic Cable,"
filed on October 4, 2000 and assigned U.S. Application Serial No. 60/237,894;
provisional patent application entitled, "Systems to Provide Video, Voice and Data
services via Fiber Optic Cable - Part 2," filed on October 26, 2000 and assigned U.S.
10 Application Serial No. 60/244,052; provisional patent application entitled, "Systems
to Provide Video, Voice and Data services via Fiber Optic Cable - Part 3," filed on
December 28, 2000 and assigned U.S. Application Serial No. 60/258,837; provisional
patent application entitled, "Protocol to Provide Voice and Data Services via Fiber
Optic Cable," filed on October 27, 2000 and assigned U.S. Application Serial No.
15 60/243,978; and provisional patent application entitled, "Protocol to Provide Voice
and Data Services via Fiber Optic Cable-Part 2," filed on May 7, 2001 and assigned
U.S. Application Serial No. 60/289,112, the entire contents of which are incorporated
by reference.

20 **TECHNICAL FIELD**

 The present invention relates to video, voice, and data communications. More
particularly, the present invention relates to a system and method for communicating
optical signals between a data service provider and one or more subscribers.

0989410-070801
FILED IN THE OFFICE OF THE
COMMISSIONER OF PATENTS AND
TRADE MARKS
MAY 10 2001
WASHINGTON, D.C.

BACKGROUND OF THE INVENTION

The increasing reliance on communication networks to transmit more complex data, such as voice and video traffic, is causing a very high demand for bandwidth. To resolve this demand for bandwidth, communication networks are relying more upon optical fibers to transmit this complex data. Conventional communication architectures that employ coaxial cables are slowly being replaced with communication networks that comprise only fiber optic cables. One advantage that optical fibers have over coaxial cables is that a much greater amount of information can be carried on an optical fiber.

The Fiber-to-the-home (FTTH) optical network architecture has been a dream of many data service providers because of the aforementioned capacity of optical fibers that enable the delivery of any mix of high-speed services to businesses and consumers over highly reliable networks. Related to FTTH is fiber to the business (FTTB). FTTH and FTTB architectures are desirable because of improved signal quality, lower maintenance, and longer life of the hardware involved with such systems. However, in the past, the cost of FTTH and FTTB architectures have been considered prohibitive. But now, because of the high demand for bandwidth and the current research and development of improved optical networks, FTTH and FTTB have become a reality.

One example of a FTTH architecture that has been introduced by the industry is a passive optical network (PON). While the PON architecture does provide an all fiber network, it has many drawbacks that make such a system impractical to implement. One drawback of the PON architecture is that too many optical cables must originate at the head end or data service hub due to limitations in the number of

times an optical signal can be divided before the signal becomes too weak to use. Another drawback can be attributed to the passive nature of a PON network. In other words, because there are no active signal sources disposed between the data service hub and the subscriber, the maximum distance that can be achieved between the data service hub and a subscriber usually falls within the range of 10 to 20 kilometers.

Another significant drawback of the PON architecture is the high cost of the equipment needed at the data service hub. For example, many PON architectures support the full service access network (FSAN) which uses the asynchronous transfer mode (ATM) protocol. To support this protocol, rather complex and expensive equipment is needed.

In addition to the high data service hub costs, conventional PON architectures do not lend themselves to efficient upgrades. That is, conventional or traditional PON architectures force physical reconfiguration of the network by adding fiber and router ports in order to increase the data speed of the network.

The data speeds in the downstream and upstream directions is another drawback of the PON architecture. Conventional PON architectures typically support up to 622 Megabit per second speeds in the downstream direction while only supporting maximum speeds of 155 Megabit per second speeds in the upstream direction. Such unbalanced communication speeds between the upstream and downstream communication directions is undesirable and is often referred to as asymmetrical bandwidth. This asymmetrical bandwidth places a low ceiling or low threshold for the amount of information that can be transferred from a subscriber to a data service hub. The asymmetrical bandwidth is a result of the high cost of optical components required.

To overcome the asymmetrical bandwidth problem and the limited distance between the subscriber and the data service hub, a conventional hybrid fiber-to-the-home (FTTH)/hybrid fiber-coax (HFC) architecture has been proposed by the industry. HFC is currently the architecture of choice for many cable television systems. In this FTTH/HFC architecture, an active signal source is placed between the data service hub and the subscriber. Typically, in this architecture, the active signal source comprises a router. This conventional router has multiple data ports that are designed to support individual subscribers. More specifically, the conventional router uses a single port for each respective subscriber. Connected to each data port of the router is an optical fiber which, in turn, is connected to the subscriber. The connectivity between data ports and optical fibers with this conventional FTTH/HFC architecture yields a very fiber intensive last mile. It is noted that the terms, "last mile" and "first mile", are both generic terms used to describe the last portion of an optical network that connects to subscribers.

In addition to a high number of optical cables originating from the router, the FTTH/HFC architecture requires radio frequency signals to be propagated along traditional coaxial cables. Because of the use of coaxial cables, numerous radio frequency (RF) amplifiers are needed between the subscriber and the data service hub. For example, RF amplifiers are typically needed every one to three kilometers in a coaxial type system. The use of coaxial cables in the FTTH/HFC architecture adds to the overall cost of the system because two separate and distinct networks are present in such an architecture. In other words, the FTTH/HFC architecture has high maintenance costs because of the completely different waveguides (coaxial cable in combination with optical fiber) in addition to the electrical and optical equipment

needed to support such two distinct systems. Stated more simply, the FTTH/HFC architecture merely combines an optical network with an electrical network where both networks run independently of one another.

Another drawback of the FTTH/HFC architecture is that the active signal source between the data service hub and subscriber, usually referred to as the router, requires a protected environment that occupies a significant amount of space. That is, the conventional router of the FTTH/HFC architecture requires an environmental cabinet that must maintain the router and related equipment at an optimum temperature. To maintain this optimum temperature, the environmental cabinet will typically include active temperature control devices for heating and cooling the cabinet.

Stated more simply, the conventional router of the FTTH/HFC architecture can only operate at standard room temperatures. Therefore, active cooling and heating units that consume power are needed to maintain such an operating temperature in all types of geographic areas and in all types of weather.

Unlike the FTTH/HFC architecture that employs two separate communication networks, another conventional hybrid fiber coax (HFC) architecture employs an active signal source between the data service hub and the subscriber that does not require a temperature controlled environmental cabinet. However, this active signal source disposed between the subscriber and the data service hub merely provides optical to electrical conversion of information signals. That is, the active signal source disposed between a subscriber and a data service hub in the HFC architecture converts downstream optical signals into electrical signals and upstream electrical signals into optical signals. The conventional HFC architecture relies upon coaxial

0999410-07991
105020" OF 165950

cable to support all signals in the last mile or so of the HFC network. Therefore, similar to the FTTH/HFC architecture, the conventional HFC architecture also requires numerous RF amplifiers on the coaxial cable side of the network.

Another drawback of the conventional HFC architecture exists at the data service hub where numerous communication devices are needed to support the data signals propagating along the optical fibers between the active signal source and the data service hub. For example, the conventional HFC architecture typically supports telephony service by using equipment known generically as a host digital terminal (HDT). The HDT can include RF interfaces on the cable side, and interfaces to either a telephone switch or to a cable carrying signals to a switch on another side.

Further, the data service hub of a conventional HFC architecture can further include a cable modem termination system (CMTS). This system provides low level formatting and transmission functions for the data transmitted between the data service hub and the subscriber. The CMTS system can operate by-directionally, meaning that it can send signals both downstream to subscribers and receive signals sent upstream from subscribers.

In addition to a CMTS, the conventional HFC architecture at the data service hub typically includes several modulators that can comprise miniature television transmitters. Each modulator can convert video signals received from satellites to an assigned channel (frequency) for transmission to subscribers. In addition to the modulators, a signal processor and other devices are used to collect the entire suite of television signals to be sent to subscribers. Typically, in a conventional HFC architecture, there can be 78 or more such modulators or processors with their

supporting equipment to service the analog TV tier. Additionally, similar equipment to serve the digital video tier is often used.

Another drawback of the conventional HFC architecture flows from the use of the CMTS. Similar to the passive optical network (PON) discussed above, the CMTS cannot support symmetrical bandwidth. That is, a bandwidth of the conventional HFC architecture is typically asymmetrical because of the use of the data over cable service interface specification (DOCSIS). The nature of the DOCSIS standard is that it limits the upstream bandwidth available to subscribers. This can be a direct result of the limited upstream bandwidth available in an HFC plant. Such a property is undesirable for subscribers who need to transmit more complex data for bandwidth intensive services such as home servers or the exchange of audio files over the Internet.

In another variation of the conventional HFC architecture, the CMTS can be part of the active signal source disposed between the subscriber and the data service hub. While this variation of the conventional HFC architecture enables the active signal source to perform some processing, the output of the active signal source in this architecture is still radio frequency energy and is propagated along coaxial cables.

Accordingly, there is a need in the art for a system and method for communicating optical signals between a data service provider and a subscriber that eliminates the use of coaxial cables and the related hardware and software necessary to support the data signals propagating along the coaxial cables. There is also a need in the art for a system and method for communicating optical signals between a data service provider and a subscriber that supports high speed symmetrical data transmission. In other words, there is a need in the art for an all fiber optical network

and method that can propagate the same bit rate downstream and upstream to/from a network subscriber. Further, there is also a need in the art for an optical network system and method that can service a large number of subscribers while reducing the number of connections at the data service hub.

5 There is also a need in the art for an active signal source that can be disposed between a data service hub and a subscriber that can be designed to withstand outdoor environmental conditions and that can be designed to hang on a strand or fit in a pedestal similar to conventional cable TV equipment that is placed within a last mile of a communications network. A further need exists in the art for a system and
10 method for receiving at least one gigabit or faster Ethernet communications in optical form from a data service hub and partition or apportion this optical bandwidth into distribution groups of a predetermined number. There is a further need in the art for a system and method that can allocate additional or reduced bandwidth based upon the demand of one or more subscribers on an optical network. Another need exists in the
15 art for an optical network system that lends itself to efficient upgrading that can be performed entirely on the network side. In other words, there is a need in the art for an optical network system that allows upgrades to hardware to take place in locations between and within a data service hub and an active signal source disposed between the data service hub and a subscriber.

20

SUMMARY OF THE INVENTION

The present invention is generally drawn to a system and method for efficient propagation of data and broadcast signals over an optical fiber network. More specifically, the present invention is generally drawn to an optical network

FOR "0" OF 6660

architecture that can include an outdoor laser transceiver, or processing node, that can be positioned in close proximity to the subscribers of an optical fiber network. For example, the outdoor laser transceiver node can be designed to withstand outdoor environmental conditions and can be designed to hang on a strand or fit in a pedestal
 5 similar to conventional cable TV equipment that is placed within “the last mile” of a network.

Unlike the conventional routers disposed between the subscriber optical interface and data service hub, the outdoor laser transceiver node does not require active cooling and heating devices that control the temperature surrounding the laser
 10 transceiver node. Further, the laser transceiver node can operate over a wide temperature range. Because the laser transceiver node does not require active temperature controlling devices, the laser transceiver node lends itself to a compact electronic packaging volume that is typically smaller than the environmental enclosures of conventional routers.

15 In contrast to conventional electronic cable TV equipment or conventional optical processing nodes, the laser transceiver node can receive at least one gigabit or faster Ethernet communications in optical form from the data service hub and partition or apportion this optical bandwidth into distribution groups of a predetermined number. In one exemplary embodiment, the laser transceiver node can
 20 partition the optical bandwidth into distribution groups comprising at least six groups of at least sixteen subscribers.

Using an appropriate protocol, the laser transceiver node can allocate additional or reduced bandwidth based upon the demand of one or more subscribers. That is, the laser transceiver node can adjust a subscriber’s bandwidth on a

FOIA b 7 - D

subscription basis or on an as-needed basis. The laser transceiver node can offer data bandwidth to the subscriber in preassigned increments. For example, the laser transceiver node can offer a particular subscriber or groups of subscribers bandwidth in units of 1, 2, 5, 10, 20, 50, 100, 200, and 450 Megabits per second (Mb/s).

5 In addition to offering bandwidth in preassigned increments, the laser transceiver node lends itself to efficient upgrading that can be performed entirely on the network side. In other words, upgrades to the hardware forming the laser transceiver node can take place in locations between and within a data service hub (such as a headend) and the laser transceiver node themselves. This means that the
10 subscriber side of the network can be left entirely intact during an upgrade to the laser transceiver node or data service hub or both.

The laser transceiver node can also provide high speed symmetrical data transmission. In other words, the laser transceiver node can propagate the same bit rates downstream and upstream from a network subscriber. Further, the laser
15 transceiver node can also serve a larger number of subscribers while reducing the number of connections at the data service hub.

The flexibility and diversity of the laser transceiver node can be attributed to at least a few components. The laser transceiver node can comprise an optical tap routing device that is coupled to one or more tap multiplexers. The optical tap routing
20 device can manage the interface with the data service hub optical signals and can route or divide or apportion the data service hub signals according to individual tap multiplexers that modulate laser transmitters to generate optical signals for specific optical taps. That is, unlike conventional routers which assign single ports to respective individual subscribers, the optical tap routing device can assign multiple

subscribers to a single port. More specifically, each tap multiplexer connected to a port of the optical tap routing device can service groups of subscribers. The individual tap multiplexers can modulate laser transmitters to supply downstream optical signals to preassigned groups of subscribers coupled to optical taps. From the optical taps, subscribers can receive the downstream optical signals with subscriber optical interfaces.

The optical tap routing device can determine which tap multiplexer is to receive a downstream electrical signal, or identify which of the plurality of optical taps originated an upstream signal. The optical tap routing device can also format data and implement the protocol required to send and receive data from each individual subscriber connected to a respective optical tap (as will be discussed below). The optical tap routing device can comprise a computer or a hardwired apparatus that executes a program defining a protocol for communications with groups of subscribers assigned to single ports. The single ports are connected to respective tap multiplexers (discussed in further detail below).

The laser transceiver node further comprises off-the-shelf hardware to generate optical signals. For example, the laser transceiver node can comprise one or more Fabry-Perot (F-P) laser transmitters, distributed feed back lasers (DFBs), or vertical cavity surface emitting lasers (VCSELs). The laser transceiver node can also support unidirectional optical signals originating from the data service hub. The laser transceiver node can combine the unidirectional optical signals with downstream optical signals so that a single optical waveguide can connect the laser transceiver node to a respective subscriber. The unidirectional optical signals can comprise broadcast video or other similar RF modulated optical signals.

The laser transceiver node is but one part of the present invention. The present invention also comprises an efficient coupler, referred to as an optical tap, between the laser transceiver node and a respective subscriber optical interface. The optical tap can divide optical signals between a plurality of subscribers and can be simple in its design. For example, each optical tap can comprise an optical splitter that may feed one or more subscribers. Optical taps can be cascaded or they can be connected in a star architecture from the laser transceiver node. The optical tap can also route signals to other optical taps that are downstream relative to a respective optical tap. The optical tap can also connect to a small number of optical waveguides so that high concentrations of optical waveguides are not present at any particular laser transceiver node. In other words, the optical tap can connect to a predetermined number of optical waveguides at a point remote from the laser transceiver node so that high concentrations of optical waveguides at the laser transceiver node can be avoided.

As noted above, the optical tap and laser transceiver node are parts of the present invention. The present invention can include a system that comprises the optical tap, the laser transceiver node, a data service hub, a subscriber optical interface, and optical waveguides connected between the optical taps and laser transceiver node.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a functional block diagram of some core components of an exemplary optical network architecture according to the present invention.

Fig. 2 is a functional block diagram illustrating an exemplary optical network architecture for the present invention.

Fig. 3 is a functional block diagram illustrating an exemplary data service hub of the present invention.

5 Fig. 4 is a functional block diagram illustrating an exemplary outdoor laser transceiver node according to the present invention.

Fig. 5 is a functional block diagram illustrating an optical tap connected to a subscriber interface by a single optical waveguide according to one exemplary embodiment of the present invention.

10 Fig. 6 is a functional block diagram illustrating an exemplary data service hub according to an alternative exemplary embodiment of the present invention where upstream optical signals and downstream optical signals are propagated along separate optical waveguides.

15 Fig. 7 is a functional block diagram illustrating an exemplary outdoor laser transceiver node that can accept upstream and downstream optical signals that are propagated along separate optical waveguides in addition to unidirectional signals that can be mixed with the downstream optical signals.

20 Fig. 8 is a functional block diagram illustrating yet another exemplary outdoor laser transceiver node that can accept optical signals propagating in separate upstream and downstream optical waveguides in addition to multiple optical waveguides that propagate unidirectional signals.

Fig. 9 is a functional block diagram illustrating another exemplary embodiment of a data service hub in which unidirectional signals such as video or RF signals are combined with downstream optical signals.

Fig. 10 is a functional block diagram illustrating another exemplary outdoor laser transceiver node that can process a combined downstream signal that comprises downstream optical signals in addition to unidirectional signals like RF transmissions or video data.

5 Fig. 11 is a functional block diagram illustrating another exemplary outdoor laser transceiver node that employs dual transceivers between tap multiplexers and respective groups of subscribers.

10 Fig. 12 is a functional block diagram illustrating another exemplary outdoor laser transceiver node that includes optical taps disposed within the laser transceiver node itself.

Fig. 13 is a logic flow diagram illustrating an exemplary method for processing unidirectional and bidirectional optical signals with a laser transceiver node of the present invention.

15 Fig. 14 is a logic flow diagram illustrating an exemplary process for handling downstream optical signals with a laser transceiver node according to the present invention.

Fig. 15 is a logic flow diagram illustrating an exemplary process for handling upstream optical signals with an exemplary laser transceiver node according to the present invention.

20 Fig. 16 is a logic flow diagram illustrating the processing of unidirectional and bidirectional optical signals with an optical tap according to the present invention.

Fig. 17 is a logic flow diagram illustrating the processing of unidirectional optical signals and bidirectional optical signals with a subscriber interface according to the present invention.

DETAILED DESCRIPTION OF EXEMPLARY EMBODIMENTS

The present invention may be embodied in hardware or software or a combination thereof disposed within an optical network. The present invention can
 5 comprise a laser transceiver node disposed between a data service hub and a subscriber that can allocate additional or reduced bandwidth based upon the demand of one or more subscribers. The present invention can support one gigabit or faster Ethernet communications in optical form to and from the data service hub and partition or apportion this optical bandwidth into distribution groups of a
 10 predetermined number. The present invention allows bandwidth to be offered to subscribers in preassigned increments. The flexibility and diversity of the present invention can be attributed to a few components.

The laser transceiver node of the present invention can comprise an optical tap routing device that is coupled to one or more tap multiplexers. The optical tap routing
 15 device can assign multiple subscribers to a single port that receives downstream optical signals from a data service hub. The laser transceiver node of the present invention can comprise off-the-shelf hardware to generate optical signals. For example, the laser transceiver node of the present invention can comprise one or more Fabry-Perot (F-P) lasers, distributed feedback lasers, or Vertical Cavity Surface
 20 Emitting Lasers (VCSELs) in the transmitters. The present invention can also comprise efficient couplers, such as optical taps, between the laser transceiver node and a respective subscriber optical interface.

The optical tap can divide optical signals among a plurality of subscribers and can be simple in its design. The optical tap can connect to a limited number of optical

waveguides at a point remote from the laser transceiver node so that high concentrations of optical waveguides at the laser transceiver node can be avoided. In another exemplary embodiment, the optical tap can be disposed within the laser transceiver node of the present invention.

5 Referring now to the drawings, in which like numerals represent like elements throughout the several Figures, aspects of the present invention and the illustrative operating environment will be described.

Figure 1 is a functional block diagram illustrating an exemplary optical network architecture **100** according to the present invention. The exemplary optical network architecture **100** comprises a data service hub **110** that is connected to outdoor laser transceiver nodes **120**. The laser transceiver nodes **120**, in turn, are connected to an optical taps **130**. The optical taps **130** can be connected to a plurality of subscriber optical interfaces **140**. Between respective components of the exemplary optical network architecture **100** are optical waveguides such as optical waveguides **150, 160, 170, and 180**. The optical waveguides **150-180** are illustrated by arrows where the arrowheads of the arrows illustrate exemplary directions of data flow between respective components of the illustrative and exemplary optical network architecture **100**. While only an individual laser transceiver node **120**, an individual optical tap **130**, and an individual subscriber optical interface **140** are illustrated in Figure 1, as will become apparent from Figure 2 and its corresponding description, a plurality of laser transceiver nodes **120**, optical taps **130**, and subscriber optical interfaces **140** can be employed without departing from the scope and spirit of the present invention. Typically, in many of the exemplary embodiments of the present

invention, multiple subscriber optical interfaces **140** are connected to one or more optical taps **130**.

The outdoor laser transceiver node **120** can allocate additional or reduced bandwidth based upon the demand of one or more subscribers that use the subscriber optical interfaces **140**. The outdoor laser transceiver node **120** can be designed to withstand outdoor environmental conditions and can be designed to hang on a strand or fit in a pedestal or "hard hole." The outdoor laser transceiver node can operate in a temperature range between minus 40 degrees Celsius to plus 60 degrees Celsius. The laser transceiver node **120** can operate in this temperature range by using passive cooling devices that do not consume power.

Unlike the conventional routers disposed between the subscriber optical interface **140** and data service hub **110**, the outdoor laser transceiver node **120** does not require active cooling and heating devices that control the temperature surrounding the laser transceiver node **120**. The present invention attempts to place more of the decision-making electronics at the data service hub **110** instead of the laser transceiver node **120**. Typically, the decision-making electronics are larger in size and produce more heat than the electronics placed in the laser transceiver node of the present invention. Because the laser transceiver node **120** does not require active temperature controlling devices, the laser transceiver node **120** lends itself to a compact electronic packaging volume that is typically smaller than the environmental enclosures of conventional routers. Further details of the components that make up the laser transceiver node **120** will be discussed in further detail below with respect to Figures 4, 7, 8, 10, 11, and 12.

In one exemplary embodiment of the present invention, three trunk optical waveguides **160**, **170**, and **180** (that can comprise optical fibers) can conduct optical signals from the data service hub **110** to the outdoor laser transceiver node **120**. It is noted that the term "optical waveguide" used in the present application can apply to
5 optical fibers, planar light guide circuits, and fiber optic pigtails and other like optical waveguides.

A first optical waveguide **160** can carry broadcast video and other signals. The signals can be carried in a traditional cable television format wherein the broadcast signals are modulated onto carriers, which in turn, modulate an optical
10 transmitter (not shown) in the data service hub **110**. A second optical waveguide **170** can carry downstream targeted services such as data and telephone services to be delivered to one or more subscriber optical interfaces **140**. In addition to carrying subscriber-specific optical signals, the second optical waveguide **170** can also propagate internet protocol broadcast packets, as is understood by those skilled in the
15 art.

In one exemplary embodiment, a third optical waveguide **180** can transport data signals upstream from the outdoor laser transceiver node **120** to the data service hub **110**. The optical signals propagated along the third optical waveguide **180** can also comprise data and telephone services received from one or more subscribers.
20 Similar to the second optical waveguide **170**, the third optical waveguide **180** can also carry IP broadcast packets, as is understood by those skilled in the art.

The third or upstream optical waveguide **180** is illustrated with dashed lines to indicate that it is merely an option or part of one exemplary embodiment according to the present invention. In other words, the third optical waveguide **180** can be

removed. In another exemplary embodiment, the second optical waveguide **170** propagates optical signals in both the upstream and downstream directions as is illustrated by the double arrows depicting the second optical waveguide **170**. In such an exemplary embodiment where the second optical waveguide **170** propagates

5 bidirectional optical signals, only two optical waveguides **160, 170** would be needed to support the optical signals propagating between the data server's hub **110** in the outdoor laser transceiver node **120**. In another exemplary embodiment (not shown), a single optical waveguide can be the only link between the data service hub **110** and the laser transceiver node **120**. In such a single optical waveguide embodiment, three

10 different wavelengths can be used for the upstream and downstream signals. Alternatively, bi-directional data could be modulated on one wavelength.

In one exemplary embodiment, the optical tap **130** can comprise an 8-way optical splitter. This means that the optical tap **130** comprising an 8-way optical splitter can divide downstream optical signals eight ways to serve eight different

15 subscriber optical interfaces **140**. In the upstream direction, the optical tap **130** can combine the optical signals received from the eight subscriber optical interfaces **140**.

In another exemplary embodiment, the optical tap **130** can comprise a 4-way splitter to service four subscriber optical interfaces **140**. Yet in another exemplary embodiment, the optical tap **130** can further comprise a 4-way splitter that is also a

20 pass-through tap meaning that a portion of the optical signal received at the optical tap **130** can be extracted to serve the 4-way splitter contained therein while the remaining optical energy is propagated further downstream to another optical tap or another subscriber optical interface **140**. The present invention is not limited to 4-way and 8-

way optical splitters. Other optical taps having fewer or more than 4-way or 8-way splits are not beyond the scope of the present invention.

Referring now to Figure 2, this Figure is a functional block diagram illustrating an exemplary optical network architecture **100** that further includes subscriber groupings **200** that correspond with a respective outdoor laser transceiver node **120**. Figure 2 illustrates the diversity of the exemplary optical network architecture **100** where a number of optical waveguides **150** connected between the outdoor laser transceiver node **120** and the optical taps **130** is minimized. Figure 2 also illustrates the diversity of subscriber groupings **200** that can be achieved with the optical tap **130**.

Each optical tap **130** can comprise an optical splitter. The optical tap **130** allows multiple subscriber optical interfaces **140** to be coupled to a single optical waveguide **150** that is connected to the outdoor laser transceiver node **120**. In one exemplary embodiment, six optical fibers **150** are designed to be connected to the outdoor laser transceiver node **120**. Through the use of the optical taps **130**, sixteen subscribers can be assigned to each of the six optical fibers **150** that are connected to the outdoor laser transceiver node **120**.

In another exemplary embodiment, twelve optical fibers **150** can be connected to the outdoor laser transceiver node **120** while eight subscriber optical interfaces **140** are assigned to each of the twelve optical fibers **150**. Those skilled in the art will appreciate that the number of subscriber optical interfaces **140** assigned to a particular waveguide **150** that is connected between the outdoor laser transceiver node **120** and a subscriber optical interface **140** (by way of the optical tap **130**) can be varied or changed without departing from the scope and spirit of the present invention. Further,

those skilled in the art recognize that the actual number of subscriber optical interfaces **140** assigned to the particular fiber optic cable is dependent upon the amount of power available on a particular optical fiber **150**.

As depicted in subscriber grouping **200**, many configurations for supplying communication services to subscribers are possible. For example, while optical tap **130_A** can connect subscriber optical interfaces **140_{A1}** through subscriber optical interface **140_{AN}** to the outdoor laser transmitter node **120**, optical tap **130_A** can also connect other optical taps **130** such as optical tap **130_{AN}** to the laser transceiver node **120**. The combinations of optical taps **130** with other optical taps **130** in addition to combinations of optical taps **130** with subscriber optical interfaces **140** are limitless. With the optical taps **130**, concentrations of distribution optical waveguides **150** at the laser transceiver node **120** can be reduced. Additionally, the total amount of fiber needed to service a subscriber grouping **200** can also be reduced.

With the active laser transceiver node **120** of the present invention, the distance between the laser transceiver node **120** and the data service hub **110** can comprise a range between 0 and 80 kilometers. However, the present invention is not limited to this range. Those skilled in the art will appreciate that this range can be expanded by selecting various off-the-shelf components that make up several of the devices of the present system.

Those skilled in the art will appreciate that other configurations of the optical waveguides disposed between the data service hub **110** and outdoor laser transceiver node **120** are not beyond the scope of the present invention. Because of the bi-directional capability of optical waveguides, variations in the number and directional flow of the optical waveguides disposed between the data service hub **110** and the

outdoor laser transceiver node **120** can be made without departing from the scope and spirit of the present invention.

Referring now to Figure 3, this functional block diagram illustrates an exemplary data service hub **110** of the present invention. The exemplary data service hub **110** illustrated in Figure 3 is designed for a two trunk optical waveguide system. That is, this data service hub **110** of Figure 3 is designed to send and receive optical signals to and from the outdoor laser transceiver node **120** along the first optical waveguide **160** and the second optical waveguide **170**. With this exemplary embodiment, the second optical waveguide **170** supports bi-directional data flow. In this way, the third optical waveguide **180** discussed above is not needed.

The data service hub **110** can comprise one or more modulators **310, 315** that are designed to support television broadcast services. The one or more modulators **310, 315** can be analog or digital type modulators. In one exemplary embodiment, there can be at least 78 modulators present in the data service hub **110**. Those skilled in the art will appreciate that the number of modulators **310, 315** can be varied without departing from the scope and spirit of the present invention.

The signals from the modulators **310, 315** are combined in a combiner **320** where they are supplied to an optical transmitter **325** where the radio frequency signals generated by the modulators **310, 315** are converted into optical form.

The optical transmitter **325** can comprise one of Fabry-Perot (F-P) Laser Transmitters, distributed feedback lasers (DFBs), or Vertical Cavity Surface Emitting Lasers (VCSELs). However, other types of optical transmitters are possible and are not beyond the scope of the present invention. With the aforementioned optical

transmitters **325**, the data service hub **110** lends itself to efficient upgrading by using off-the-shelf hardware to generate optical signals.

The optical signals generated by the optical transmitter (often referred to as the unidirectional optical signals) are propagated to amplifier **330** such as an Erbium
5 Doped Fiber Amplifier (EDFA) where the unidirectional optical signals are amplified. The amplified unidirectional optical signals are then propagated out of the data service hub **110** via a unidirectional signal output port **335** which is connected to one or more first optical waveguides **160**.

The unidirectional signal output port **335** is connected to one or more first
10 optical waveguides **160** that support unidirectional optical signals originating from the data service hub **110** to a respective laser transceiver node **120**. The data service hub **110** illustrated in Figure 3 can further comprise an Internet router **340**. The data service hub **110** can further comprise a telephone switch **345** that supports telephony service to the subscribers of the optical network system **100**. However, other
15 telephony service such as Internet Protocol telephony can be supported by the data service hub **110**. If only Internet Protocol telephony is supported by the data service hub **110**, then it is apparent to those skilled in the art that the telephone switch **345** could be eliminated in favor of lower cost VoIP equipment. For example, in another exemplary embodiment (not shown), the telephone switch **345** could be substituted
20 with other telephone interface devices such as a soft switch and gateway. But if the telephone switch **345** is needed, it may be located remotely from the data service hub **110** and can be connected through any of several conventional means of interconnection.

The data service hub **110** can further comprise a logic interface **350** that is connected to a laser transceiver node routing device **355**. The logic interface **350** can comprise a Voice over Internet Protocol (VoIP) gateway when required to support such a service. The laser transceiver node routing device **355** can comprise a conventional router that supports an interface protocol for communicating with one or more laser transceiver nodes **120**. This interface protocol can comprise one of gigabit or faster Ethernet, Internet Protocol (IP) or SONET protocols. However, the present invention is not limited to these protocols. Other protocols can be used without departing from the scope and spirit of the present invention.

The logic interface **350** and laser transceiver node routing device **355** can read packet headers originating from the laser transceiver nodes **120** and the internet router **340**. The logic interface **350** can also translate interfaces with the telephone switch **345**. After reading the packet headers, the logic interface **350** and laser transceiver node routing device **355** can determine where to send the packets of information.

The laser transceiver node routing device **355** can supply downstream data signals to respective optical transmitters **325**. The data signals converted by the optical transmitters **325** can then be propagated to a bi-directional splitter **360**. The optical signals sent from the optical transmitter **325** into the bi-directional splitter **360** can then be propagated towards a bi-directional data input/output port **365** that is connected to a second optical waveguide **170** that supports bi-directional optical data signals between the data service hub **110** and a respective laser transceiver node **120**. Upstream optical signals received from a respective laser transceiver node **120** can be fed into the bi-directional data input/output port **365** where the optical signals are then forwarded to the bi-directional splitter **360**. From the bi-directional splitter **360**,

respective optical receivers **370** can convert the upstream optical signals into the electrical domain. The upstream electrical signals generated by respective optical receivers **370** are then fed into the laser transceiver node routing device **355**. Each optical receiver **370** can comprise one or more photoreceptors or photodiodes that
5 convert optical signals into electrical signals.

When distances between the data service hub **110** and respective laser transceiver nodes **120** are modest, the optical transmitters **325** can propagate optical signals at 1310 nm. But where distances between the data service hub **110** and the laser transceiver node are more extreme, the optical transmitters **325** can propagate
10 the optical signals at wavelengths of 1550 nm with or without appropriate amplification devices.

Those skilled in the art will appreciate that the selection of optical transmitters **325** for each circuit may be optimized for the optical path lengths needed between the data service hub **110** and the outdoor laser transceiver node **120**. Further, those
15 skilled in the art will appreciate that the wavelengths discussed are practical but are only illustrative in nature. In some scenarios, it may be possible to use communication windows at 1310 and 1550 nm in different ways without departing from the scope and spirit of the present invention. Further, the present invention is not limited to a 1310 and 1550 nm wavelength regions. Those skilled in the art will
20 appreciate that smaller or larger wavelengths for the optical signals are not beyond the scope and spirit of the present invention.

Referring now to Figure 4, this Figure illustrates a functional block diagram of an exemplary outdoor laser transceiver node **120** of the present invention. In this exemplary embodiment, the laser transceiver node **120** can comprise a unidirectional

optical signal input port **405** that can receive optical signals propagated from the data service hub **110** that are propagated along a first optical waveguide **160**. The optical signals received at the unidirectional optical signal input port **405** can comprise broadcast video data. The optical signals received at the input port **405** are propagated to an amplifier **410** such as an Erbium Doped Fiber Amplifier (EDFA) in which the optical signals are amplified. The amplified optical signals are then propagated to a splitter **415** that divides the broadcast video optical signals among diplexers **420** that are designed to forward optical signals to predetermined subscriber groups **200**.

The laser transceiver node **120** can further comprise a bi-directional optical signal input/output port **425** that connects the laser transceiver node **120** to a second optical waveguide **170** that supports bi-directional data flow between the data service hub **110** and laser transceiver node **120**. Downstream optical signals flow through the bi-directional optical signal input/output port **425** to an optical waveguide transceiver **430** that converts downstream optical signals into the electrical domain. The optical waveguide transceiver further converts upstream electrical signals into the optical domain. The optical waveguide transceiver **430** can comprise an optical/electrical converter and an electrical/optical converter.

Downstream and upstream electrical signals are communicated between the optical waveguide transceiver **430** and an optical tap routing device **435**. The optical tap routing device **435** can manage the interface with the data service hub optical signals and can route or divide or apportion the data service hub signals according to individual tap multiplexers **440** that communicate optical signals with one or more optical taps **130** and ultimately one or more subscriber optical interfaces **140**. It is

noted that tap multiplexers **440** operate in the electrical domain to modulate laser transmitters in order to generate optical signals that are assigned to groups of subscribers coupled to one or more optical taps.

Optical tap routing device **435** is notified of available upstream data packets as they arrive, by each tap multiplexer **440**. The optical tap routing device is connected to each tap multiplexer **440** to receive these upstream data packets. The optical tap routing device **435** relays the packets to the data service hub **110** via the optical waveguide transceiver **430**. The optical tap routing device **435** can build a lookup table from these upstream data packets coming to it from all tap multiplexers **440** (or ports), by reading the source IP address of each packet, and associating it with the tap multiplexer **440** through which it came. This lookup table can then used to route packets in the downstream path. As each packet comes in from the optical waveguide transceiver **430**, the optical tap routing device looks at the destination IP address (which is the same as the source IP address for the upstream packets). From the lookup table the optical tap routing device can determine which port is connected to that IP address, so it sends the packet to that port. This can be described as a normal layer 3 router function as is understood by those skilled in the art.

The optical tap routing device **435** can assign multiple subscribers to a single port. More specifically, the optical tap routing device **435** can service groups of subscribers with corresponding respective, single ports. The optical taps **130** coupled to respective tap multiplexers **440** can supply downstream optical signals to pre-assigned groups of subscribers who receive the downstream optical signals with the subscriber optical interfaces **140**.

In other words, the optical tap routing device **435** can determine which tap multiplexers **440** is to receive a downstream electrical signal, or identify which of a plurality of optical taps **130** propagated an upstream optical signal (that is converted to an electrical signal). The optical tap routing device **435** can format data and implement the protocol required to send and receive data from each individual subscriber connected to a respective optical tap **130**. The optical tap routing device **435** can comprise a computer or a hardwired apparatus that executes a program defining a protocol for communications with groups of subscribers assigned to individual ports. One exemplary embodiment of the program defining the protocol is discussed in copending and commonly assigned provisional patent application entitled, "Protocol to Provide Voice and Data Services via Fiber Optic Cable," filed on October 27, 2000 and assigned U.S. Application Serial No. 60/243,978, the entire contents of which are incorporated by reference. Another exemplary embodiment of the program defining the protocol is discussed in copending and commonly assigned provisional patent application entitled, "Protocol to Provide Voice and Data Services via Fiber Optic Cable-Part 2," filed on May 7, 2001 and assigned U.S. Application Serial No. 60/289,112, the entire contents of which are incorporated by reference.

The single ports of the optical tap routing device are connected to respective tap multiplexers **440**. With the optical tap routing device **435**, the laser transceiver node **120** can adjust a subscriber's bandwidth on a subscription basis or on an as-needed or demand basis. The laser transceiver node **120** via the optical tap routing device **435** can offer data bandwidth to subscribers in pre-assigned increments. For example, the laser transceiver node **120** via the optical tap routing device **435** can offer a particular subscriber or groups of subscribers bandwidth in units of 1, 2, 5, 10,

20, 50, 100, 200, and 450 Megabits per second (Mb/s). Those skilled in the art will appreciate that other subscriber bandwidth units are not beyond the scope of the present invention.

Electrical signals are communicated between the optical tap routing device
5 **435** and respective tap multiplexers **440**. The tap multiplexers **440** propagate optical signals to and from various groupings of subscribers. Each tap multiplexer **440** is connected to a respective optical transmitter **325**. As noted above, each optical transmitter **325** can comprise one of a Fabry-Perot (F-P) laser, a distributed feedback laser (DFB), or a Vertical Cavity Surface Emitting Laser (VCSEL). The optical
10 transmitters produce the downstream optical signals that are propagated towards the subscriber optical interfaces **140**. Each tap multiplexer **440** is also coupled to an optical receiver **370**. Each optical receiver **370**, as noted above, can comprise photoreceptors or photodiodes. Since the optical transmitters **325** and optical receivers **370** can comprise off-the-shelf hardware to generate and receive respective
15 optical signals, the laser transceiver node **120** lends itself to efficient upgrading and maintenance to provide significantly increased data rates.

Each optical transmitter **325** and each optical receiver **370** are connected to a respective bi-directional splitter **360**. Each bi-directional splitter **360** in turn is connected to a diplexer **420** which combines the unidirectional optical signals
20 received from the splitter **415** with the downstream optical signals received from respective optical receivers **370**. In this way, broadcast video services as well as data services can be supplied with a single optical waveguide such as a distribution optical waveguide **150** as illustrated in Figure 2. In other words, optical signals can be

coupled from each respective diplexer **420** to a combined signal input/output port **445** that is connected to a respective distribution optical waveguide **150**.

Unlike the conventional art, the laser transceiver node **120** does not employ a conventional router. The components of the laser transceiver node **120** can be disposed within a compact electronic packaging volume. For example, the laser transceiver node **120** can be designed to hang on a strand or fit in a pedestal similar to conventional cable TV equipment that is placed within the "last," mile or subscriber proximate portions of a network. It is noted that the term, "last mile," is a generic term often used to describe the last portion of an optical network that connects to subscribers.

Also because the optical tap routing device **435** is not a conventional router, it does not require active temperature controlling devices to maintain the operating environment at a specific temperature. In other words, the laser transceiver node **120** can operate in a temperature range between minus 40 degrees Celsius to 60 degrees Celsius in one exemplary embodiment.

While the laser transceiver node **120** does not comprise active temperature controlling devices that consume power to maintain temperature of the laser transceiver node **120** at a single temperature, the laser transceiver node **120** can comprise one or more passive temperature controlling devices **450** that do not consume power. The passive temperature controlling devices **450** can comprise one or more heat sinks or heat pipes that remove heat from the laser transceiver node **120**. Those skilled in the art will appreciate that the present invention is not limited to these exemplary passive temperature controlling devices. Further, those skilled in the art will also appreciate the present invention is not limited to the exemplary operating

temperature range disclosed. With appropriate passive temperature controlling devices **450**, the operating temperature range of the laser transceiver node **120** can be reduced or expanded.

In addition to the laser transceiver node's **120** ability to withstand harsh outdoor environmental conditions, the laser transceiver node **120** can also provide high speed symmetrical data transmissions. In other words, the laser transceiver node **120** can propagate the same bit rates downstream and upstream to and from a network subscriber. This is yet another advantage over conventional networks, which typically cannot support symmetrical data transmissions as discussed in the background section above. Further, the laser transceiver node **120** can also serve a large number of subscribers while reducing the number of connections at both the data service hub **110** and the laser transceiver node **120** itself.

The laser transceiver node **120** also lends itself to efficient upgrading that can be performed entirely on the network side or data service hub **110** side. That is, upgrades to the hardware forming the laser transceiver node **120** can take place in locations between and within the data service hub **110** and the laser transceiver node **120**. This means that the subscriber side of the network (from distribution optical waveguides **150** to the subscriber optical interfaces **140**) can be left entirely in-tact during an upgrade to the laser transceiver node **120** or data service hub **110** or both.

The following is provided as an example of an upgrade that can be employed utilizing the principles of the present invention. In one exemplary embodiment of the invention, the subscriber side of the laser transceiver node **120** can service six groups of 16 subscribers each for a total of up to 96 subscribers. Each group of 16 subscribers can share a data path of about 450 Mb/s speed. Six of these paths

represents a total speed of $6 \times 450 = 2.7$ Gb/s. In the most basic form, the data communications path between the laser transceiver node **120** and the data service hub **110** can operate at 1 Gb/s. Thus, while the data path to subscribers can support up to 2.7 Gb/s, the data path to the network can only support 1 Gb/s. This means that not all of the subscriber bandwidth is useable. This is not normally a problem due to the statistical nature of bandwidth usage.

An upgrade could be to increase the 1 Gb/s data path speed between the laser transceiver node **120** and the data service hub **110**. This may be done by adding more 1 Gb/s data paths. Adding one more path would increase the data rate to 2 Gb/s, approaching the total subscriber-side data rate. A third data path would allow the network-side data rate to exceed the subscriber-side data rate. In other exemplary embodiments, the data rate on one link could rise from 1 Gb/s to 2 Gb/s then to 10 Gb/s, so when this happens, a link can be upgraded without adding more optical links.

The additional data paths (bandwidth) may be achieved by any of the methods known to those skilled in the art. It may be accomplished by using a plurality of optical waveguide transceivers **430** operating over a plurality of optical waveguides, or they can operate over one optical waveguide at a plurality of wavelengths, or it may be that higher speed optical waveguide transceivers **430** could be used as shown above. Thus, by upgrading the laser transceiver node **120** and the data service hub **110** to operate with more than a single 1 Gb/s link, a system upgrade is effected without having to make changes at the subscribers' premises.

Referring now to Figure 5, this Figure is a functional block diagram illustrating an optical tap **130** connected to a subscriber optical interface **140** by a single optical waveguide **150** according to one exemplary embodiment of the present

invention. The optical tap **130** can comprise a combined signal input/output port that is connected to another distribution optical waveguide that is connected to a laser transceiver node **120**. As noted above, the optical tap **130** can comprise an optical splitter **510** that can be a 4-way or 8-way optical splitter. Other optical taps having
5 fewer or more than 4-way or 8-way splits are not beyond the scope of the present invention. The optical tap can divide downstream optical signals to serve respective subscriber optical interfaces **140**. In the exemplary embodiment in which the optical tap **130** comprises a 4-way optical tap, such an optical tap can be of the pass-through type, meaning that a portion of the downstream optical signals is extracted or divided
10 to serve a 4-way splitter contained therein, while the rest of the optical energy is passed further downstream to other distribution optical waveguides **150**.

The optical tap **130** is an efficient coupler that can communicate optical signals between the laser transceiver node **120** and a respective subscriber optical interface **140**. Optical taps **130** can be cascaded, or they can be connected in a star
15 architecture from the laser transceiver node **120**. As discussed above, the optical tap **130** can also route signals to other optical taps that are downstream relative to a respective optical tap **130**.

The optical tap **130** can also connect to a limited or small number of optical waveguides so that high concentrations of optical waveguides are not present at any
20 particular laser transceiver node **120**. In other words, in one exemplary embodiment, the optical tap can connect to a limited number of optical waveguides **150** at a point remote from the laser transceiver node **120** so that high concentrations of optical waveguides **150** at a laser transceiver node can be avoided. However, those skilled in the art will appreciate that the optical tap **130** can be incorporated within the laser

transceiver node **120** as will be discussed in further detail below with respect to another exemplary embodiment of the laser transceiver node **120** as illustrated in Figure 12.

The subscriber optical interface **140** functions to convert downstream optical signals received from the optical tap **130** into the electrical domain that can be processed with appropriate communication devices. The subscriber optical interface **140** further functions to convert upstream electrical signals into upstream optical signals that can be propagated along a distribution optical waveguide **150** to the optical tap **130**. The subscriber optical interface **140** can comprise an optical diplexer **515** that divides the downstream optical signals received from the distribution optical waveguide **150** between a bi-directional optical signal splitter **520** and an analog optical receiver **525**. The optical diplexer **515** can receive upstream optical signals generated by a digital optical transmitter **530**. The digital optical transmitter **530** converts electrical binary/digital signals to optical form so that the optical signals can be transmitted back to the data service hub **110**. Conversely, the digital optical receiver **540** converts optical signals into electrical binary/digital signals so that the electrical signals can be handled by processor **550**.

The present invention can propagate the optical signals at various wavelengths. However, the wavelength regions discussed are practical and are only illustrative of exemplary embodiments. Those skilled in the art will appreciate that other wavelengths that are either higher or lower than or between the 1310 and 1550 nm wavelength regions are not beyond the scope of the present invention.

The analog optical receiver **525** can convert the downstream broadcast optical video signals into modulated RF television signals that are propagated out of the

modulated RF unidirectional signal output **535**. The modulated RF unidirectional signal output **535** can feed to RF receivers such as television sets (not shown) or radios (not shown). The analog optical receiver **525** can process analog modulated RF transmission as well as digitally modulated RF transmissions for digital TV applications.

The bi-directional optical signal splitter **520** can propagate combined optical signals in their respective directions. That is, downstream optical signals entering the bi-directional optical splitter **520** from the optical the optical diplexer **515**, are propagated to the digital optical receiver **540**. Upstream optical signals entering it from the digital optical transmitter **530** are sent to optical diplexer **515** and then to optical tap **130**. The bi-directional optical signal splitter **520** is connected to a digital optical receiver **540** that converts downstream data optical signals into the electrical domain. Meanwhile the bi-directional optical signal splitter **520** is also connected to a digital optical transmitter **530** that converts upstream electrical signals into the optical domain.

The digital optical receiver **540** can comprise one or more photoreceptors or photodiodes that convert optical signals into the electrical domain. The digital optical transmitter can comprise one or more lasers such as the Fabry-Perot (F-P) Lasers, distributed feedback lasers, and Vertical Cavity Surface Emitting Lasers (VCSELs).

The digital optical receiver **540** and digital optical transmitter **530** are connected to a processor **550** that selects data intended for the instant subscriber optical interface **140** based upon an embedded address. The data handled by the processor **550** can comprise one or more of telephony and data services such as an Internet service. The processor **550** is connected to a telephone input/output **555** that

can comprise an analog interface. The processor **550** is also connected to a data interface **560** that can provide a link to computer devices, set top boxes, ISDN phones, and other like devices. Alternatively, the data interface **560** can comprise an interface to a Voice over Internet Protocol (VoIP) telephone or Ethernet telephone.

5 The data interface **560** can comprise one of Ethernet's (10BaseT, 100BaseT, Gigabit) interface, HPNA interface, a universal serial bus (USB) an IEEE1394 interface, an ADSL interface, and other like interfaces.

Referring now to Figure 6, this figure is a functional block diagram illustrating an exemplary data service hub **110B** according to an alternative exemplary
10 embodiment of the present invention where upstream optical signals and downstream optical signals are propagated along separate optical waveguides such as the second optical waveguide **170** and the third optical waveguide **180** discussed above with respect to Figure 1. In other words, in this exemplary embodiment, the second optical waveguide **170** is designed to carry only downstream optical signals while the third
15 optical waveguide **180** is designed to carry only upstream optical signals from the laser transceiver node **120**.

The exemplary data service hub **110B** further comprises a downstream optical signal output port **605** that is coupled to the second optical waveguide **170**. The data service hub **110B** further comprises an upstream optical signal input port that is
20 coupled to the third optical waveguide **180**. With the exemplary data service hub **110B** separate optical waveguides **180** and **170** carry the respective upstream and downstream optical transmissions. With this exemplary embodiment, power can be conserved since additional components that were previously used to combine and separate the upstream and downstream optical signals are eliminated.

This exemplary embodiment of the data service hub **110B** can further reduce distance limitations due to power loss and cross talk. In other words, at each end of an optical transmitter, which is supplying a lot of optical power compared with the received power, can create interference at the receiver due to incomplete isolation
5 between the upstream and downstream optical signal directions. By utilizing separate optical waveguides for the upstream and downstream optical signals, this interference can be substantially reduced or eliminated.

Referring now to Figure 7, this Figure illustrates a functional block diagram of an exemplary outdoor laser transceiver node **120B** that can accept upstream and
10 downstream optical signals that are propagated along separate optical waveguides in addition to unidirectional signals that can be mixed with downstream optical signals. In other words, the laser transceiver node **120B** can be coupled to the exemplary data service hub **110B** illustrated in Figure 6.

The laser transceiver node **120B** can comprise a downstream optical signal
15 input port **705** that is coupled to the second optical waveguide **170** as illustrated in Figure 1. The downstream optical signal input port **705** is coupled to an optical receiver **710** that converts the downstream optical signals into the electrical domain. The optical receiver **710** in turn, feeds the electrical signals to the optical tap routing device **435**.

20 The laser transceiver node **120B** of Figure 7 can further comprise an optical transmitter **720** that converts electrical signals received from the optical tap routing device **435** into the optical domain. The optical signals generated by the optical transmitter **720** are fed to an upstream optical signal output port **715**. The upstream optical signal output port **715** is coupled to the third optical waveguide **180** as

illustrated in Figure 1. Compared to the exemplary laser transceiver node **120A** illustrated in Figure 4, the bi-directional splitter **360** has been replaced with a second diplexer **420₂**. The optical transmitter **325** generates optical signals of a wavelength that is higher than the upstream optical signals produced by a respective subscriber optical interface **140**. For example, in one exemplary embodiment, the optical transmitter **325** can produce optical signals having wavelengths between 1410 and 1490 nm while the upstream optical signals remain at the 1310 nm wavelength region.

As noted above, those skilled in the art will appreciate that the wavelengths discussed are only illustrative in nature. In some scenarios, it may be possible to use communication windows at 1310 and 1550 nm in different ways without departing from the scope and spirit of the present invention. Further, the present invention is not limited to the wavelength regions discussed above. Those skilled in the art will appreciate that smaller or larger wavelengths for the optical signals are not beyond the scope and spirit of the present invention.

Because of the difference in wavelength regions between the upstream and downstream optical signals, the additional diplexer **420** can be substituted for the previous bi-directional splitter **360** (illustrated in the exemplary embodiment of Figure 4). The additional or substituted diplexer **420** does not exhibit the same loss as the previous bi-directional splitter **360** that is used in the exemplary embodiment of Figure 4. This substitution of the bi-directional splitter **360** with the additional diplexer **420** can also be applied to the subscriber optical interface **140**. That is, when the upstream and downstream optical signals are operating at respective different wavelength regions, the bi-directional optical signal splitter **520** of the subscriber optical interface **140** can be substituted with a diplexer **420**. The substitution of the

bi-directional splitter **360** with the diplexer **420** can reduce the optical loss between the laser transceiver node **120** and the subscriber optical interface **140**.

Alternatively, if the laser transceiver node **120** is using the same wavelengths for the upstream and downstream optical signals, the optical interface **140** uses the bi-directional optical signal splitter **520** with a corresponding loss in optical power as illustrated in Figure 5. Those skilled in the art will appreciate that various other substitutions for the components of the laser transceiver node **120** can be made without departing from the scope and spirit of the present invention.

Referring now to Figure 8, this Figure illustrates another exemplary outdoor, laser transceiver node **120C** that can accept optical signals propagating from separate upstream and downstream optical waveguides in addition to multiple optical waveguides that propagate unidirectional signals. In this exemplary embodiment, the laser transceiver node **120C** of Figure 8 can comprise multiple unidirectional signal input ports **805** that are coupled to a plurality of first optical waveguides **160**. In this exemplary embodiment, compared to the laser transceiver node **120A** of Figure 4 and laser transceiver node **120B** of Figure 7, the amplifier **410** has been removed from the laser transceiver node **120C** as illustrated in Figure 8. The amplifier **410** is taken out of the laser transceiver node **120C** and placed in the data service hub **110**.

The optical signals propagating from the multiple first optical waveguides **160** are combined with the upstream and downstream optical signals originating from the second set of diplexers **420₂** using the first set of diplexers **420₁**. This design to remove the amplifier **410** (that typically comprises an Erbium Doped Fiber Amplifier - EDFA) from the laser transceiver node **120C** of Figure 8 to the data service hub **110** and to include multiple first optical waveguides **160** feeding into the laser transceiver

node **120C**, may be made on the basis of economics and optical waveguide availability.

Figure 9 illustrates another exemplary embodiment of a data service hub **110D** in which unidirectional signals such as video or RF signals are combined with downstream optical signals. In this exemplary embodiment, the data service hub **110D** further comprises a splitter **415** that feeds the broadcast video optical signals to respective diplexers **420**. The respective diplexers **420** combine the broadcast video optical signals with the downstream data optical signals produced by respective optical transmitters **325**. In this way, the first optical waveguide **160** as illustrated in Figure 1 can be eliminated since the broadcast video optical signals are combined with the downstream data optical signals along the second optical waveguide **170**.

Figure 10 illustrates another exemplary laser transceiver node **120D** that can be coupled to the data service hub **110D** as illustrated in Figure 9. In this exemplary embodiment, the laser transceiver node **120D** comprises a combined downstream optical signal input **1005** that is coupled to a second optical waveguide **160** that provides a combined downstream optical signal comprising broadcast video services and data service. The laser transceiver node **120D** further comprises a diplexer **420** that feeds the broadcast video or RF signals to an amplifier **410**. The broadcast video or RF optical signals are then sent to a splitter **415** which then sends the optical signals to the first set of diplexers **420₁**. The combination of the data service hub **110D** as illustrated in Figure 9 and the laser transceiver node **120D** as illustrated in Figure 10 conserves optical waveguides between these two devices.

As noted above, in another exemplary embodiment, it may be possible to use only a single fiber (not shown) to operatively link a data service hub **110** and a laser

transceiver node **120**. In such an exemplary embodiment, different wavelengths could be used to propagate upstream and downstream optical signals.

Figure 11 is a functional block diagram illustrating another exemplary outdoor laser transceiver node **120E** that employs dual transceivers between tap multiplexers **440** and respective groups of subscribers. In this embodiment the downstream optical signals originating from each respective tap multiplexer **440** are split immediately after the tap multiplexer **440**. In this exemplary embodiment, each optical transmitter **325** is designed to service only eight subscribers as opposed to sixteen subscribers of other embodiments. But each tap multiplexer **440** typically services sixteen or fewer subscribers.

In this way, the splitting loss attributed to the optical taps **130** can be substantially reduced. For example, in other exemplary embodiments that do not split the downstream optical signals immediately after the tap multiplexer **440**, such embodiments are designed to service sixteen or fewer subscribers with a corresponding theoretical splitting loss of approximately 14 dB (including an allowance for losses). With the current exemplary embodiment that services eight or fewer subscribers, the theoretical splitting loss is reduced to approximately 10.5 dB.

In laser transceiver node **120E**, the optical receivers **370** cannot be paralleled because at all times one receiver **370** or the other is receiving signals from respective subscribers, while the other receiver **370** is not receiving signals. The receiver **370** not receiving any upstream optical signals could output noise which would interfere with reception from the receiver **370** receiving upstream optical signals. Therefore, a switch **1105** can be employed to select the optical receiver **370** that is currently receiving an upstream optical signal. The tap multiplexer can control the switch **1105**

since it knows which optical receiver 370 should be receiving upstream optical signals at any given moment of time.

Figure 12 is a functional block diagram illustrating another exemplary outdoor laser transceiver node 120F that includes optical taps 130 disposed within the laser transceiver node 120F itself. In this architecture, optical waveguides 150 from each subscriber optical interface 140 can be connected to the laser transceiver node 120F. Typically, the number of optical waveguides 150 that are connected to the laser transceiver node 120F is such that two laser transceiver nodes 150 are needed to support the number of optical waveguides 150. But when less than a maximum number of subscribers exist, one laser transceiver node 120F can be used to service the existing service base. When the service base expands to a number requiring an additional laser transceiver node 120, the additional laser transceiver nodes can be added.

By placing the optical taps 130 within the laser transceiver node 120F, two or more laser transceiver nodes 120F can be co-located with one another for the reason discussed above. In other words, this exemplary embodiment enables two or more laser transceiver nodes 120F to be placed in close proximity to one another. Such placement of laser transceiver nodes 120F can conserve power and result in significant cost savings. Furthermore, with such a co-location design, future expansion of the optical architecture 100 can easily be obtained. That is, one laser transceiver nodes 120F can be installed until more subscribers join the optical network architecture 100 requiring the laser transceiver node. Optical waveguides 150 can be connected to the co-located laser transceiver nodes as more subscribers join the optical network architecture 100.

Referring now to Figure 13, this figure illustrates an exemplary method for processing unidirectional and bi-directional optical signals with a laser transceiver node **120** of the present invention. Basically, Figure 13 provides an overview of the processing performed by the laser transceiver node **120**.

5 Certain steps in the process described below must naturally precede others for the present invention to function as described. However, the present invention is not limited to the order of the steps described if such order or sequence does not alter the functionality of the present invention. That is, it is recognized that some steps may be performed before or after other steps without departing from the scope and spirit of
10 the present invention.

Step **1305** is the first step in the exemplary laser transceiver node overview process **1300**. In step **1305**, downstream RF modulated optical signals are amplified by the amplifier **410** as illustrated in Figure 4. As noted above, the amplifier **410** can comprise an Erbium Doped Fiber Amplifier (EDFA). However, other optical
15 amplifiers are not beyond the scope of the present invention.

Next, in Step **1307**, bandwidth between respective subscribers can be apportioned with the optical tap routing device **435**. In other words, the optical tap routing device **435** can adjust a subscriber's bandwidth in accordance with a subscription or on an as-needed basis. The optical tap routing device **435** can offer a
20 particular subscriber or groups of subscribers bandwidth in units of 1, 2, 5, 10, 20, 50, 100, 200, and 450 Mb/s.

In Step **1310**, the downstream RF modulated optical signals are combined with the downstream optical signals originating from the tap multiplexers **440**. The

combining of the downstream optical signals can occur in diplexers 420. Subsequently, in Step 1315, the combined downstream optical signals are propagated along the distribution optical waveguides 150 to respective assigned groups of optical taps 200.

5 In Step 1320, upstream optical signals are received by optical receivers 370 and then converted to upstream electrical signals. The upstream electrical signals are sent to respective tap multiplexers 440. Electrical signals received from respective tap multiplexers 440 are combined in the optical tap routing device 435 according to Step 1325. Also in Step 1325, the upstream electrical signals from the optical tap
10 routing device 435 can be converted into the optical domain with either an optical waveguide transceiver 430 or an optical transmitter 720. In Step 1330, the upstream optical signals are propagated towards the data service hub 110 via a bi-directional optical waveguide 170 or a dedicated upstream optical waveguide 180.

Referring now to Figure 14, this figure illustrates a logic flow diagram of an
15 exemplary process for handling downstream optical signals with a laser transceiver node 120 according to the present invention. More specifically, the logic flow diagram of Figure 14 illustrates an exemplary method for communicating optical signals from a data service provider 110 to at least one subscriber.

As noted above, certain steps in the process described below must naturally
20 proceed others for the present invention to function as described. However, the present invention is not limited to the order of steps described if such order or sequence does not alter the functionality of the present invention. That is, it is

recognized that some steps may be performed before or after other steps without departing from the scope and spirit of the present invention.

Step **1405** is the first step in the exemplary process **1400** for communicating optical signals from a data service provider to at least one subscriber. In step **1405**,
5 downstream optical signals are received at the laser transceiver node **120**. For example, downstream optical signals can be received at the unidirectional optical signal input port **405** as illustrated in Figure 4. Further, downstream optical signals can also be received at the bi-directional optical signal input/output port **425** also illustrated in Figure 4.

10 Next in Step **1410**, the downstream optical signals can be converted to the electrical domain. In other words, the downstream optical signals received at the bi-directional output signal input/output port **425** can be converted into the electrical domain with an optical waveguide transceiver **430**. As noted above, the optical waveguide transceiver **430** can comprise an optical/electrical converter. Next, in Step
15 **1415** the optical tap routing device **435** can divide the converted electrical signals between tap multiplexers **440** that are assigned to groups of optical taps **130**. In Step **1420**, the downstream bandwidth can be apportioned for subscribers with the optical tap routing device **435**.

20 In this step, the optical tap routing device **435** can apportion bandwidth to groups of subscribers based upon a subscription or based upon a current demand. The optical tap routing device **435** can partition the bandwidth in units of 1, 2, 5, 10, 20, 50, 100, 200, and 450 Mb/s. However, the present invention is not limited to these increments. Other increments of bandwidth are not beyond the scope and spirit of the

present invention. The optical tap routing device 435 can apportion bandwidth in this way by executing a program defining a protocol for communications with groups of subscribers assigned to single ports. The single ports are connected to the respective tap multiplexers 440.

5 In Step 1425, the downstream electrical signals processed by the optical tap routing device 435 are multiplexed with the tap multiplexers 440. Subsequently, in Step 1430 the downstream electrical signals can be converted into downstream optical signals with the optical transmitters 325. As noted above, the optical transmitters 325 can comprise one of Fabry-Perot (F-P) lasers, distributed feedback lasers, and Vertical
10 Cavity Surface Emitting Lasers (VCSELs). However, as noted above, other types of lasers are not beyond the scope of the present invention.

In Step 1435 the unidirectional RF modulated optical signals received from the first optical waveguide 160 can be split into a plurality of paths with a splitter 415. Next, in Step 1440 the downstream paths of the RF modulated optical signals are
15 combined with the paths of the downstream optical signals originating from the tap multiplexers 440.

Figure 15 illustrates a logic flow diagram of an exemplary process for handling upstream optical signals with an exemplary laser transceiver node 120 according to the present invention. More specifically, Figure 15 illustrates a process
20 for communicating optical signals from at least one subscriber to a data service provider hub.

As noted above, certain steps in the process described below must naturally proceed others for the present invention to function as described. However, the

present invention is not limited to the order of the steps described if such order or sequence does not alter the functionality of the present invention. That is, it is recognized that some steps may be performed before or after other steps without departing from the scope and spirit of the present invention.

5 Step **1505** is the first step in the exemplary laser transceiver node upstream process **1500**. In Step **1505**, upstream optical signals originating from subscribers to optical taps **130** are propagated along distribution optical waveguides **150**. Next, the upstream optical signals are converted by a optical receiver **370** in Step **1510**. In Step **1515**, the upstream electrical signals are combined at the optical tap routing device
10 **435**. Next, in Step **1520** upstream bandwidth for subscribers is apportioned with the optical tap routing device **435** similar to how the downstream optical bandwidth is apportioned as discussed above with respect to Figure 14.

For the upstream optical signals, the optical tap routing device **435** can employ time division multiple access (TDMA) in order to service or support signals
15 originating from multiple tap multiplexers **440**. As may be apparent to those skilled in the art, in time division multiple access the optical tap routing device **435** switches in time from one tap multiplexer **440** to another tap multiplexer **440**. In contrast, for the downstream optical signals, the optical tap routing device **435** employs time division multiplexing (TDM). As is apparent to those skilled in the art, time division
20 multiplexing occurs when the optical tap routing device **435** sends data to multiple tap multiplexers **440**. In time division multiplexing, the signal is never removed, so receiving clocks remain synchronized.

In Step **1525**, the combined upstream electrical signals are converted to upstream optical signals with either the optical waveguide transceiver **430** or the optical transmitter **720**. Next, in Step **1530**, the combined upstream optical signals are propagated along an optical waveguide such as the second optical waveguide **170** or
5 third optical waveguide **180** to the data service hub **110**.

Figure 16 is a logic flow diagram illustrating the processing of unidirectional and bi-directional optical signals with an optical tap **130** according to the present invention. As noted above, certain steps in the process described below must naturally proceed others for the present invention to function as described. However,
10 the present invention is not limited to the order of steps described if such order or sequence does not alter the functionality of the present invention. That is, it is recognized that some steps may be performed before or after other steps without departing from the scope and spirit of the present invention.

Step **1605** is the first step in the optical tap process **1600**. Step **1605** diverts
15 signals from an optical waveguide such as a distribution optical waveguide **150** coupled to a laser transceiver node to the combined signal input/output port **505**. Next in Step **1610** downstream optical signals that were tapped are split with the optical splitter **510**. The optical splitter **510** can split the downstream optical signals to one or more subscriber interfaces or other taps or splitters or combination thereof
20 via distribution optical waveguides **150**. In Step **1615**, the downstream tap combined optical signals can be propagated to and upstream optical signal from respective subscribers can be received and combined with the optical splitter **510**.

Figure 17 is a logic flow diagram illustrating exemplary processing of unidirectional optical signals and bi-directional optical signals with a subscriber optical interface **140** according to the present invention. As noted above, certain steps in the process described below must naturally proceed others for the present invention to function as described. However, the present invention is not limited to the order of steps described if such order or sequence does not alter the functionality of the present invention. That is, it is recognized that some steps may be performed before or after other steps without departing from the scope and spirit of the present invention.

Step **1705** is the first step in the subscriber optical interface process **1700**. In Step **1705**, combined downstream optical signals are received with an optical diplexer **515**. Next, in Step **1710**, the RF modulated downstream optical signals are separated from the downstream data optical signals originating from the tap multiplexers **440**. In Step **1715**, the downstream RF modulated optical signals are converted to downstream electrical optical signals with an analog optical receiver **525**. As noted above, the analog optical receiver **525** can handle both analog modulated signals in addition to digitally modulated signals for digital TV applications.

In Step **1720**, the upstream electrical signals are converted to optical signals with the digital optical transmitter **530**. As noted above, the digital optical transmitter **530** can comprise one of a Fabry-Perot (F-P) laser, a distributed feedback (DFB) laser, and a vertical cavity surface emitting laser (VCSEL) or other similar lasers. The upstream electrical signals can be generated from a telephone input/output port **555** or a data interface **560** or both (as discussed above).

In Step 1725, downstream electrical signals emitted from the digital optical receiver 540 are received by a processor 550. The processor 550, in turn, propagates these electrical signals to appropriate output devices such as the telephone input/output port 555 or data interface 560 or both. As noted above, the telephone
5 input/output port 555 or the data interface 560 or both can generate upstream electrical signals that are sent to the processor 550 and then converted into the optical domain with the digital optical transmitter 530.

Those skilled in the art will appreciate that the optical network architecture 100 of the present invention can provide at least one of video, telephone, and
10 computer communication services via the optical signals. Also, those skilled in the art will appreciate that the video layer comprising the RF modulated signals can be removed from the exemplary optical network architecture 100 without departing from the scope and spirit of the present invention.

With the present invention, an all fiber optical network and method that can
15 propagate the same bit rate downstream and upstream to/from a network subscriber are provided. Further, the present invention provides an optical network system and method that can service a large number of subscribers while reducing the number of connections at the data service hub.

The present invention also provides an active signal source that can be
20 disposed between a data service hub and a subscriber and that can be designed to withstand outdoor environmental conditions. The present invention can also be designed to hang on a strand or fit in a pedestal similar to conventional cable TV equipment that is placed within a last mile of a communications network. The system and method of the present invention can receive at least one Gigabit or faster Ethernet

communications in optical form from a data service hub and partition or apportion this optical bandwidth into distribution groups of a predetermined number. The system and method of the present invention can allocate additional or reduced bandwidth based upon the demand of one or more subscribers on an optical network.

5 Additionally, the optical network system of the present invention lends itself to efficient upgrading that can be performed entirely on the network side. In other words, the optical network system allows upgrades to hardware to take place in locations between and within a data service hub and an active signal source disposed between the data service hub and a subscriber.

10 It should be understood that the foregoing relates only to illustrate the embodiments of the present invention, and that numerous changes may be made therein without departing from the scope and spirit of the invention as defined by the following claims.

15